

DUPLI-COLOR AEROSOL ART

Ord.-no.: look at ordering information

Technical Information



Fast-drying acrylic-based quality for numerous application possibilities. Special spray system, which is even used by famous graffiti artists. A broad range of the best-selling colours, mainly matching to RAL. Also available as clear coat. Suitable for wood, metal, paper, glass or paintable hard plastics as well as for many textiles. Also applicable for the designing of finery, concrete and natural stone.

Quality & properties

- High-grade acrylic quality
- Very good coverage
- Excellent adhesion on many surfaces
- Especially suitable for indoor objects
- Dust dry in 10 min.
- Good flow, smooth surface
- Polishable surface
- Weather-resistant, light-proof, UV-resistant
- Permanent shade- and gloss resistant
- Scratch-, shock- and impact-resistant

Physical & chemical data

- Base: Acrylic resin
- Colourname:
 - ◊ zinc yellow
 - ◊ golden yellow
 - ◊ ivory
 - ◊ colza yellow
 - ◊ melon yellow
 - ◊ deep orange
 - ◊ signal red
 - ◊ traffic red
 - ◊ traffic purple
 - ◊ brilliant blue
 - ◊ gentian blue
 - ◊ sky blue
 - ◊ traffic blue
 - ◊ water blue
 - ◊ leaf green
 - ◊ moss green
 - ◊ grass green
 - ◊ yellow green
 - ◊ silver grey
 - ◊ agate grey
 - ◊ sepia brown
 - ◊ cream
 - ◊ grey white
 - ◊ beige
 - ◊ maize yellow
 - ◊ brown beige
 - ◊ saffron yellow
 - ◊ grey beige
 - ◊ vermilion
 - ◊ pure orange
 - ◊ flame red
 - ◊ ruby red
 - ◊ purple red
 - ◊ red violet
 - ◊ blue lilac
 - ◊ ultramarine blue
 - ◊ light blue
 - ◊ cobalt blue
 - ◊ pigeon blue
 - ◊ turquoise green
 - ◊ pastel green
 - ◊ traffic green
 - ◊ light green
 - ◊ iron grey

- ◊ stone grey
- ◊ clay brown
- ◊ red brown
- ◊ jet black
- ◊ pure white
- ◊ light grey
- ◊ heather violet
- ◊ sand yellow
- ◊ daffodil yellow
- ◊ pastel orange
- ◊ azure blue
- ◊ anthracite grey
- ◊ black grey
- ◊ blue grey
- ◊ pebble grey
- ◊ white aluminium
- ◊ grey aluminium
- ◊ traffic white
- ◊ traffic black
- ◊ nut brown
- ◊ chocolate brown
- ◊ oyster white
- ◊ capri blue
- ◊ olive green
- ◊ window grey
- ◊ dusty grey
- ◊ silk grey
- ◊ light ivory
- ◊ traffic yellow
- ◊ broom yellow
- ◊ wine red
- ◊ oxide red
- ◊ telemagenta
- ◊ sapphire blue
- ◊ emerald green
- ◊ reseda green
- ◊ may green
- ◊ squirrel grey
- ◊ basalt grey
- ◊ slate grey
- ◊ concrete grey
- ◊ graphite grey
- ◊ traffic grey A
- ◊ telegrey 4
- ◊ ochre brown
- ◊ copper brown
- ◊ black brown
- ◊ signal white
- ◊ graphite black
- ◊ papyrus white
- ◊ signal yellow
- ◊ yellow orange
- ◊ carmine red
- ◊ signal blue
- ◊ pine green
- ◊ telegrey 2
- ◊ traffic orange
- ◊ black red
- ◊ turquoise blue
- ◊ mint green
- ◊ traffic grey b
- ◊ steel blue
- ◊ rosa
- ◊ pastel blue
- Smell: Characteristic
- Degree of gloss:
 - ◊ semi mat, 25 ±5 GU
 - ◊ gloss, >75 GU
 - ◊ mat, 10 ±2 GU
- Efficiency: 400 ML – 0.8 - 1.5 m²
- Dry to touch: 30 min
- Dust dry: 10 min
- Completely dry: 2 h
- Overcoatable: 24 h
- Surfaces: wood, metal, paper, glass or paintable hard plastics as well as for many textiles
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure:
 - ◊ 8300/20 bar
 - ◊ 23/20 bar

- Flash point: n.a.
- Storage stability: 10 y
- Content: 400 ML

How to use

- The surface has to be clean, dry and free from fat.
- Remove residues of old paintings and rust, then sand and prime if necessary. Let dry for 1 - 2 hours.
- Use Pastic Primer on plastic parts.
- Cover areas not to be painted.
- Before use, shake the can for 3 minutes.
- Test spray at an invisible spot to check colour-matching and compatibility of the lacquer.
- Spray from a distance of approx. 25 cm several thin coats.
- Do not spray over synthetic paints.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of February 26, 2024 – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim - info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega - info-nl@european-aerosols.com