

DUPLI-COLOR CEMENT LOOK

Ord.-no.: 521621, 521638

Technical Information



Fast-drying cement-effect. For applications on all kinds of surfaces. Depending on layer thickness, it is possible to achieve different drying-conditions, like real cement. By spraying a last fine mist, it's even possible to achieve a mineral feel. Please use mat clear coat for outdoor using.

Quality & properties

- Polystyrene-resistant acrylic lacquer with a special solvent
- Very good coverage
- Excellent adhesion on many materials, e.g. polystyrene, metal, wood, glass, ceramics, eternite, concrete, stone, paper, cardboard, coatable hard plastics, flowers etc.
- Good flow, smooth surface
- Dries quick and evenly
- Suitable for painting and repairing indoors and outdoors objects
- Resistant to wiping
- Weather-resistant, light-proof, UV-resistant
- Scratch-, bump- and shock-proof

Physical & chemical data

- Base: Acrylate copolymers
- Colourname: grey
- Smell: Characteristic
- Efficiency: 400 ML – 1 m²
- Dry to touch: 30 min
- Dust dry: 10 min
- Completely dry: 24 h
- Surfaces: polystyrene, metal, wood, glass, ceramics, eternite, concrete, stone, paper, cardboard, coatable hard plastics, flowers.
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 8300/20 bar
- Temperature Resistance: – 80 °C
- Storage stability: 10 y
- Content: 400 ML

How to use

- Remove rust and dirt.
- The ground has to be clean, dry and free from fat.
- Possibly existing old paintings and smooth surfaces have to be roughened with fine sand paper.
- Mask off areas not to be painted.
- Before use, shake can for 3 minutes.
- Test spray at an invisible spot.
- Spray from a distance of approx. 25 cm several thin coats.
- Do not spray over surfaces which are painted with synthetic resin lacquer!

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labeling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of January 15, 2024 – This release replaces all eventually earlier issued versions.